



FS-N10

Fiber Amplifier, Zero-line Expansion Unit





Specifications

Model		FS-N10
Туре		0-line
Main unit/expansion unit		Expansion unit (No output cable)
Control output		N/A*1
Light source LED		Red, 4-element LED
APC		ON/OFF switchable (Factory setting: OFF)
Response time		$50~\mu s$ (HIGH SPEED) /250 μs (FINE) /500 μs (TURBO) /1 ms (SUPER) /4 ms (ULTRA) /16 ms (MEGA)
Number of interference prevention units		0 for HIGH SPEED; 4 for FINE; 8 for TURBO/SUPER/ULTRA/MEGA (When set to double, the number of interference-prevention units will be doubled.)
Unit expansion		Up to 16 units can be connected total (two output type is treated as two units)
Rating	Power voltage	12 to 24 VDC ±10 %, Ripple (P-P) 10 % or less
	Current Consumption	Normal: 900 mW or less (36 mA max. at 24 V, 48 mA max. at 12 V) *2 Eco on mode: 800 mW or less (32 mA max. at 24 V, 39 mA max. at 12 V) *2 Eco Full mode: 470 mW or less (19 mA max. at 24 V, 23 mA max. at 12 V)
Environmental resistance	Ambient light	Incandescent lamp: 20,000 lux or less, Sunlight: 30,000 lux or less
	Ambient temperature	-20 to +55 °C -4 to +131 °F (No freezing)*3
	Relative humidity	35 to 85 % RH (No condensation)
	Vibration resistance	10 to 55 Hz, Double amplitude 1.5 mm 0.06", 2 hours in each of the X, Y, and Z directions
	Shock resistance	500 m/s², 3 times in each of the X, Y, and Z directions
Case material		Both main unit and expansion unit housing material: Polycarbonate
Weight		Approx. 20 g

^{*1} Counted as 1 output when connecting with the network unit NU Series.

When using 2-outputs, one unit is counted as two units. All temperature regulations are for when the unit is mounted on a DIN rail and installed on metal sheeting.

^{*2} Increases 100 mW (4.0 mA) for High Speed mode

 $^{^{*3}}$ One or two more units connected: -20 to +55 °C (-4 to +131 °F); 3 to 10 more units connected: -20 to +50 °C (-4 to +122 °F); 11 to 16 more units connected: -20 to +45 °C (-4 to +113 °F).



Dimensions

* Download CAD file or product manual for larger image/text and more detail.

FS-N10





