



Potentiometer, Classical, M22, 22.5 mm, R 1 kΩ, P 0.5 W, Bezel: titanium

Part no. M22-R1K
229489
EL Number 4355458
(Norway)

General specifications	
Product name	Eaton Moeller® series M22 Potentiometer
Part no.	M22-R1K
EAN	4015082294892
Product Length/Depth	70 millimetre
Product height	29 millimetre
Product width	29 millimetre
Product weight	0.034 kilogram
Compliances	CE Marked
Certifications	UL 508 IEC 60947-5 CSA Std. C22.2 No. 14-05 EN 60947-5 CSA Std. C22.2 No. 94-91 VDE CE IEC/EN 60947-5 UL CSA-C22.2 No. 94-91 UL Category Control No.: NKCR IEC/EN 60947 CSA-C22.2 No. 14-05 CSA Class No.: 3211-03 UL File No.: E29184 CSA File No.: 012528 VDE 0660 CSA
Product Tradename	M22
Product Type	Potentiometer
Product Sub Type	None
Features & Functions	
Bezel color	Titanium
Design	Classical
Electric connection type	Screw connection
Fitted with:	3 individual screw terminals
General information	
Accuracy	± 10 % (linear), Resistance value
Degree of protection	IP66 NEMA Other
Lifespan, mechanical	25,000 Operations
Opening diameter	22.5 mm
Overvoltage category	III
Pollution degree	3
Rated impulse withstand voltage (Uimp)	4000 V AC
Type	Potentiometer
Ambient conditions, mechanical	
Mounting position	As required
Shock resistance	Mechanical, According to IEC/EN 60068-2-27 30 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms
Climatic environmental conditions	
Ambient operating temperature - min	-25 °C
Ambient operating temperature - max	70 °C
Climatic proofing	Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
Terminal capacities	

Terminal capacity (solid)		0.5 - 1.5 mm ²
Terminal capacity (stranded)		0.5 - 1.5 mm ²
Tightening torque		0.5 Nm, Screw terminals
Electrical rating		
Power consumption		0.5 W
Rated insulation voltage (Ui)		250 V
Rated power		0.5 V·A
Resistance		1000 Ohm
Communication		
Connection to SmartWire-DT		No
Design verification		
Equipment heat dissipation, current-dependent Pvid		0 W
Heat dissipation capacity Pdis		0 W
Heat dissipation per pole, current-dependent Pvid		0 W
Rated operational current for specified heat dissipation (In)		0 A
Static heat dissipation, non-current-dependent Pvs		0.5 W
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Please enquire
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Potentiometer for command devices (EC001027)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Potentiometer for command devices (ecl@ss13-27-37-12-27 [AKF045019])			
Resistance		Ohm	1000
Power consumption		W	0.5
Hole diameter		mm	22.5
Number of revolutions			1 - 1
Type of electric connection			Screw connection
Degree of protection (IP)			IP66
Degree of protection (NEMA)			Other