

# Rittal – The System.

Faster – better – everywhere.



## SK 3302.300

# TopTherm wall-mounted cooling unit Blue e

State: 14/11/2024 (Source: [rittal.com/uk-en](http://rittal.com/uk-en))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# SK 3302.300 - TopTherm wall-mounted cooling unit Blue e 0.3 - 4 kW

Energy-efficient Blue e wall-mounted cooling units in the output categories 300 W to 4000 W and with integral electrical condensate evaporator (from 1000 W). Available in the special formats "horizontal" and "flat".



## Features

|   |   |
|---|---|
| Model No.                               | SK 3302.300   |
| Design                                  | wall-mounted<br>Horizontal  |
| Product description                     | Energy-efficient Blue e wall-mounted cooling units in the output categories 300 W to 4000 W and with integral electrical condensate evaporator (from 1000 W).   |
| Benefits                                | May be linked to the IoT interface via Blue e IoT adaptor for cooling units from 500 W cooling output with e-Comfort controller                                 |
| Material                                | Sheet steel   |
| Colour                                  | RAL 7035  |
| Supply includes                         | Condenser with hydrophobic RiNano coating<br>Fully wired ready for connection (plug-in terminal strip)<br>Drilling template<br>Assembly parts                   |
| Total cooling output to<br>DIN EN 14511 | Cooling output L35 L35/50 Hz: 0.3 kW<br>Cooling output L35 L35/60 Hz: 0.32 kW<br>Cooling output L35 L50/50 Hz: 0.16 kW<br>Cooling output L35 L50/60 Hz: 0.17 kW |
| Rated operating voltage                 | 230 V, 1~, 50 Hz/60 Hz  |

# Features

|  |   |
|--|---|
| Rated current max.                             | At 50 Hz: 1.6 A<br>At 60 Hz: 1.7 A  |
| Start-up current max.                          | At 50 Hz: 4.3 A<br>At 60 Hz: 5.3 A  |
| Air throughput (unimpeded air flow)            | External circuit: 310 m <sup>3</sup> /h<br>Internal circuit: 310 m <sup>3</sup> /h  |
| Energy efficiency ratio (EER) 50/60 Hz L35 L35 | Refrigeration factor L35 L35 (EER) 50 Hz: 1<br>Refrigeration factor L35 L35 (EER) 60 Hz: 1  |
| Design   | wall-mounted  |
| Special design                                 | Horizontal  |
| Dimensions                                     | Width: 525 mm<br>Height: 340 mm<br>Depth: 153 mm  |
| Protection category to IEC 60 529              | External circuit IP 34<br>Internal circuit IP 54  |
| Protection category NEMA                       | UL Type 12  |
| Refrigerant/cooling medium                     | Refrigerant: R-513A<br>Quantity: 0.15 kg<br>Global Warming Potential (GWP): 631<br>CO <sub>2</sub> equivalent (CO <sub>2</sub> e): 0.09 t                                   |
| Temperature control                            | Basic controller (factory setting +35 °C)   |
| Operating temperature range                    | 10 °C...53 °C   |
| Operating temperature max @60 Hz               | 52 °C   |
| Storage temperature range                      | -40 °C...70 °C  |
| Setting range                                  | 30 °C...52 °C   |
| Power consumption Pel                          | Power consumption L35 L35/50 Hz: 0.3 kW<br>Power consumption L35 L35/60 Hz: 0.32 kW<br>Power consumption L35 L50/50 Hz: 0.33 kW<br>Power consumption L35 L50/60 Hz: 0.35 kW |
| Permissible operating pressure (p. max.)       | 25 bar  |

# Features

---

|                       |                                      |
|-----------------------|--------------------------------------|
| Pre-fuse              | Miniature circuit-breaker/fuse: 10 A |
| Packs of              | 1 pc(s).                             |
| Weight/pack           | 13 kg                                |
| Net weight            | 14.07                                |
| Gross weight          | 15.64                                |
| Customs tariff number | 84158200                             |
| EAN                   | 4028177429796                        |
| ETIM 8                | EC000855                             |
| ETIM 7.0              | EC000855                             |
| ECLASS 8.0            | 27180704                             |

# Approvals

---

|              |   |
|--------------|---|
| Approvals    | 30 - KC Korea<br>UL + C-UL (listed)<br>UL + C-UL - FTTA<br>UR + C-UR (recognized)                         |
| Certificates | EAC   |
| Explanations | Declaration of conformity<br>Declaration of conformity - F-gas regulation<br>Declaration of conformity UK |