



D4NS-4DF

Plástico 3NC M20

Especificaciones

Door switch type	Key-operated
Guard-lock	×
Material housing	Resin
Material head	Resin
Ambient temperature (operating)	-30-70 °C
Direction of operation	Adjustable
Door contacts NC	3
Door contacts NO	0
Switch action	Slow action
Make before break	×
LED indicator	×
Connection method	Terminal block
Cable length	0 m
Degree of protection (IP)	IP67
Conduit size	M20
Number of conduits	1
Shape	Cuboid
Overall length of sensor	96 mm
Height of sensor	30 mm
Width of sensor	31 mm



D4DS-K1

Pasador horizontal D4NS



D4DS-K2

Pasador vertical D4NS



D4DS-K3

Pasador angular D4NS



D4DS-K5

Pasador ajustable horizontal/vertical

Descargas

Librería CAD



D4NS Safety-door Switch
Datasheet

ES PDF 1,2 MB



D4NS/D4NS-SK Safety-door Switch
Datasheet

EN PDF 3,85 MB



EAC Mark removal
Aviso de discontinuación

EN PDF 221 KB



Machine Safety
Catálogo

ES PDF 14,5 MB



Machine Safety Solution
Catálogo

EN PDF 2,86 MB



Safety Component Selection Guide
Catálogo

ES PDF 2,95 MB



Safety Interlock Switches
Catálogo

ES PDF 1,54 MB



Safety Solution Advanced Guide
Guía

EN PDF 2,57 MB



Safety Solution Basic Guide
Guía

EN PDF 14,4 MB

TÉRMINOS DE USO DEL SITIO WEB

Este documento PDF se generó a partir del sitio web europeo de OMRON Industrial Automation el 19 November, 2024. Haga clic aquí para acceder a los [legal](#).

OMRON

INDUSTRIAL AUTOMATION | INDUSTRIAL.OMRON.EU