

Basic features

Approval/Conformity	CE cULus EAC WEEE
Operating panel	2 buttons 320° rotation 4-digit, 7-segment display, red

Display/Operation

Switching function display	LED
----------------------------	-----

Electrical connection

Connection	M12x1-Male, 4-pin, A-coded
Polarity reversal protected	yes
Short-circuit protection	yes

Electrical data

Current draw max.	50 mA
Load cycles	100 mil.
Operating voltage U_b	18...36 VDC
Output current max.	500 mA
Protection class	III
Switching cycles min.	100 mil.
Switching frequency	200 Hz

Environmental conditions

Ambient temperature	-40...85 °C
Compensation temperature	-25...85 °C
EN 60068-2-27, Shock	30 g, 11 ms
EN 60068-2-6, Vibration	30 g, 10...2000 Hz
IP rating	IP67
Interference immunity	EN 61000-6-2: 2005
Media temperature	-40...125 °C
Noise emission	EN 61326-2-3: 2013
Storage temperature	-40...85 °C
Temperature coefficient typ.	$\leq \pm 0.1\%$ FSO/10K

Functional safety

MTTF (40 °C)	368 a
--------------	-------

Interface

Analog output	Analog, current 4...20 mA
Switching output	PNP normally open/normally closed (NO/NC)

Material

Connector housing, material	1.4307 stainless steel
Gasket, material	FKM
Housing material	Stainless steel (1.4301) PA 6.6
Measuring cell, material	1.4435 stainless steel
Process connection material	1.4404 stainless steel

Mechanical data

Process connection	G 1/2" (DIN 3852) front-flush
Tightening torque max.	10 Nm
Weight	350.00 g

Range/Distance


Accuracy	±0.5 % FSO BFSL
Burst pressure	120.00 bar
Long-term stability max.	0.3 % FSO/year
Measuring range	0...20 bar
Overload pressure	80 bar
Repeat accuracy	≤ ± 0.2 % FSO
Resolution	≤ 12 bits
Sampling rate	1 ms

Remarks

vacuum-tight
 Permissible burden on analog output Rmax = 330 Ohm
 For more information about MTTF and B10d see MTTF / B10d Certificate

Indication of the MTTF- / B10d value does not represent a binding composition and/or life expectancy assurance; these are simply experiential values with no warranty implications. These declared values also do not extend the expiration period for defect claims or affect it in any way.

Connector Drawings



Wiring Diagrams (Schematic)

