






E3ZM-T86

Metálica cc 3h Barrera 15m PNP M8

Especificaciones

Shape	Cuboid
Sensing method	Through-beam
Sensing distance	15000 mm
Setting method	Manual adjustment
Connection method	Connector M8 - 4 pin
Output type	PNP
Operation mode	Dark-ON, Light-ON
Response time	1 ms
Material housing	Stainless steel
Thread size	Other
Product Width (unpacked)	10.8 mm
Product Height (unpacked)	32.2 mm
Product Depth (unpacked)	21 mm
Type of light	Infrared light
Power supply voltage	10-30 V
Degree of protection (IP)	IP67/IP69K

	E39-L150	Soporte de montaje ajuste vertical E3Z/E3S-R 65mm
	E39-L151	Soporte de montaje ajuste vertical E3Z/E3S-R 165mm
	E39-L203	Soporte de montaje para sensor E3AS, montaje trasero
	E39-L211	Soporte de montaje para sensor E3AS, forma en L
	E39-L212	Soporte de montaje de protección para E3AS, montaje vertical
	E39-L214	Cubierta metálica de protección para E3AS, montaje en superficie horizontal
	E39-L44	Soporte de montaje posterior E3Z

Productos relacionados:



Conectores y juegos de cables M8

Juegos de cables y conectores industriales para cualquier aplicación

Librería CAD



E3Z

Catálogo

ES PDF 1,27 MB



**E3ZM Photoelectric
Sensor, Compact,
Stainless steel**

Datasheet

ES PDF 993 KB



EAC Mark removal

**Aviso de
discontinuación**

EN PDF 221 KB